

Codice/Part number	Ø int. /	Ø est. /	Spess. min/	Spess. max/	Peso/	PE/	PS/	Depr./	Curvatura/	Lg. Rotolo/	Vol.	Lg. spirulina/
	ins.Ø	out.Ø	min wall thick.	max wall thick.	Weight	WP	BP	Vac.	Bending	Coil Lgth.	[m <sup>3</sup> ]	Banding coil Lgth.
	[mm]	[mm]	[mm]	[mm]	[g/m]	bar	bar	[m H <sub>2</sub> O]	[mm]	[m]		[mm]
<b>WT010380000000</b>	38,1	51,5	3,0	6,7	725	10	30	9,5	90	30	0,132	153
<b>WT010400000000</b>	40	53,3	3,0	6,7	745	8	24	9,5	100	30	0,137	152
<b>WT010500000000</b>	50	65,4	3,0	7,7	1085	7	21	9,5	160	30	0,283	179,1
<b>WT010508000000</b>	50,8	66,2	3,0	7,7	1100	7	21	9,5	160	30	0,286	179,1
<b>WT010600000000</b>	60	76,8	3,0	8,4	1230	7	21	9,5	180	30	0,442	202,3
<b>WT010760000000</b>	76,2	95,7	3,5	9,8	1900	6	18	9,0	200	30	0,736	225
<b>WT010800000000</b>	80	100,7	3,5	10,3	2180	6	18	9,0	210	30	0,774	225
<b>WT011000000000</b>	100	120,8	3,5	10,4	2585	6	18	9,0	300	30	0,928	240
<b>WT011020000000</b>	101,6	122,6	3,5	10,5	2655	6	18	9,0	300	30	0,942	240
<b>WT011270000000</b>	127	151,9	5,0	12,5	3965	5	15	9,0	380	30	1,824	292,5
<b>WT011520000000</b>	152,4	180,0	5,0	15,0	5225	5	15	8,0	450	20	1,456	322,5
<b>WT012030000000</b>	203,2	236,0	6,0	16,4	8245	4	12	8,0	600	10	1,888	375

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

\*Available on request, contact our sales office for more info and quantities