

Codice/Part number	Ø int. / ins.Ø	Ø est. / out.Ø	Peso/ Weight	PE/WP	PS/BP	Depres./ Vacuum	Curvatura/ Bending rad.	Lungh.rotolo/ Coil Lgth.	Volume
	[mm]	[mm]	[g/m]	bar	bar	[m H ₂ O]	[mm]	[m]	[m ³]
B3 01 012.0 020.0	12*	20	280	19	57	10	36	60	0,039
B3 01 020.0 029.0	20*	29	475	14	42	10	60	60	0,106
B3 01 025.0 035.0	25	35	655	12	36	10	75	60	0,146
B3 01 030.0 040.0	30	40	765	12	36	9	90	60	0,184
B3 01 032.0 043.0	32	43	890	11	33	9	96	60	0,214
B3 01 035.0 046.0	35	46	960	10	30	9	105	60	0,225
B3 01 038.0 049.0	38	49	1030	10	30	9	110	30	0,198
B3 01 040.0 051.0	40	51	1080	10	30	9	120	30	0,202
B3 01 045.0 058.0	45	58	1505	9	27	8	140	30	0,241
B3 01 050.0 063.0	50	63	1650	8	24	8	150	30	0,286
B3 01 060.0 074.0	60*	74	2080	7	21	8	180	30	0,363
B3 01 063.0 077.0	63	77	2175	7	21	8	190	30	0,379
B3 01 070.0 085.0	70*	85	2525	6	18	7	210	30	0,469
B3 01 076.0 091.0	76	91	2685	6	18	7	230	30	0,603
B3 01 080.0 095.0	80*	95	2790	6	18	7	240	20	0,498
B3 01 090.0 106.0	90*	106	3435	5	15	7	270	20	0,760
B3 01 102.0 118.0	102*	118	3850	4	12	7	310	20	0,801

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

*Available on request, contact our sales office for more info and quantities