VULCANO PU HDS 15 ESTERE

+90° C
-40° C
峰值/*peaks*
125° C

半透明聚酯型聚氨酯软管，包塑镀铜钢丝螺旋增强 内壁平滑，确保介质流动性能；所有内径恒定壁厚1.5mm，可根据需求提供永久抗静电版本。软管两端螺旋钢丝接地可导静电。

•适用于重磨损型应用，如塑料行业运输系统，喷丸处理中，输送高研磨性颗粒，球粒，碎片；也可用于运输砂砾，石块和集料。

包塑镀铜螺旋钢丝
TPU coated copper colored steel spiral



聚酯型TPU软管 / *Ester based TPU hose*

Translucent ester based Polyurethane hose, reinforced with a high adhesion TPU coated copper colored steel spiral. *Smooth inside to ensure optimization of flow properties. Constant wall thickness of 1.5 mm throughout the range; on request it can be made with permanent antistatic material. It can be made conductive by earthing the steel spiral.*
• Suitable for heavy duty application: passage of highly abrasive granules, pellets and chips, conveying systems in plastic industry, shotblast. To transport gravel, stones and aggregate.

技术参数 / *Technical data*

代码 Code	内径 Ø Int.	最小壁厚 Min wall th.	重量 Weight	弯曲半径 Bending	负压. Vac.	卷长 Coil lgth.	体积 Vol.	桥式卡箍W2 double bridge W2
	mm	mm	g/m	mm	m H_2O	m	m^3	
VC 01 020.0 000.0	20*	1,50	245	25	9,5	20	0,040	
VC 01 025.0 000.0	25*	1,50	305	30	9,5	20	0,050	
VC 01 030.0 000.0	30*	1,50	440	35	9,5	20	0,060	
VC 01 032.0 000.0	32*	1,50	465	35	9,5	20	0,060	
VC 01 035.0 000.0	35*	1,50	500	40	9,5	20	0,060	
VC 01 038.0 000.0	38	1,50	535	40	9,5	20	0,090	
VC 01 040.0 000.0	40	1,50	560	50	9,5	20	0,090	
VC 01 045.0 000.0	45*	1,50	620	50	9,0	20	0,100	
VC 01 050.0 000.0	50	1,50	685	60	9,0	20	0,110	
VC 01 051.0 000.0	51	1,50	695	60	9,0	20	0,120	
VC 01 060.0 000.0	60	1,50	810	70	8,5	20	0,130	
VC 01 063.0 000.0	63	1,50	845	70	8,0	20	0,140	
VC 01 065.0 000.0	65*	1,50	870	70	7,5	20	0,190	
VC 01 070.0 000.0	70	1,50	1005	80	7,5	20	0,200	
VC 01 076.0 000.0	76	1,50	1090	90	7,0	20	0,250	
VC 01 080.0 000.0	80	1,50	1140	90	6,0	20	0,260	F2 W2 076.0 090.0
VC 01 090.0 000.0	90	1,50	1275	100	5,0	20	0,290	
VC 01 100.0 000.0	100*	1,50	1410	120	4,0	15	0,320	
VC 01 102.0 000.0	102	1,50	1435	120	3,5	15	0,320	
VC 01 110.0 000.0	110*	1,50	1545	130	3,2	15	0,350	F2 W2 100.0 127.0
VC 01 115.0 000.0	115*	1,50	1610	135	3,0	15	0,360	
VC 01 120.0 000.0	120	1,50	1675	140	3,0	15	0,370	
VC 01 127.0 000.0	127	1,50	2075	150	2,9	15	0,400	
VC 01 130.0 000.0	130*	1,50	2120	150	2,6	15	0,610	
VC 01 140.0 000.0	140	1,50	2275	160	2,4	15	0,650	
VC 01 150.0 000.0	150*	1,50	2435	170	2,0	15	0,690	
VC 01 152.0 000.0	152	1,50	2465	170	2,0	15	0,700	F2 W2 130.0 190.0
VC 01 160.0 000.0	160	1,50	2590	180	1,8	15	0,740	
VC 01 175.0 000.0	175*	1,50	2705	200	1,5	15	0,950	
VC 01 180.0 000.0	180	1,50	2780	210	1,5	15	0,980	
VC 01 200.0 000.0	200*	1,50	3080	230	1,2	15	1,080	
VC 01 203.0 000.0	203	1,50	3125	230	1,2	15	1,100	F2 W2 200.0 230.0
VC 01 228.0 000.0	228*	1,50	3500	260	1,0	10	1,230	
VC 01 250.0 000.0	250*	1,50	3830	290	0,8	10	1,340	
VC 01 254.0 000.0	254	1,50	3890	290	0,8	10	1,360	
VC 01 279.0 000.0	279*	1,50	4265	320	0,7	10	1,490	F2 W2 250.0 330.0
VC 01 305.0 000.0	305	1,50	5680	350	0,7	定制		
VC 01 320.0 000.0	320*	1,50	5955	N.D.	0,7	定制		
VC 01 350.0 000.0	350*	1,50	6500	N.D.	0,7	定制		
VC 01 400.0 000.0	400*	1,50	7415	N.D.	0,7	定制		F2 W2 350.0 410.0
VC 01 406.0 000.0	406*	1,50	7525	N.D.	0,7	定制		
VC 01 500.0 000.0	500*	1,50	9240	600	0,2	5	1,306	

*如有需求，请与销售办事处联系，以获得更多的信息和数据 / *Available on request,contact our sales office for more info and quantities

以上技术数据均在温度23℃和相对湿度50%下测量 / The technical data *here reported were measured at 23°c with 50% humidity*

可提供导电版软管在第29页 / *Available also in the electrical conductive version, pag. 29*

本公司保留随时更改产品规格及停止生产的权利，恕不另行通知
We reserve the right either to alter speci ications and discontinue products without prior notice