


# EOLO PUP EST



透明聚酯型聚氨酯软管，深灰色防震硬质PVC螺旋增强 内壁光滑，外壁波纹状；耐磨性抗弯性能优异；壁厚范围0.8-1.0mm；可根据需求定制导电带铜线版本。

• 适用于塑料，木工，陶瓷行业以及需要良好耐磨性的应用中，抽吸输送磨损型粉末，如：粉末，球团，颗粒，纤维和灰尘等。

*Transparent ester based Polyurethane hose, reinforced with a dark grey anti-shock PVC spiral. Completely smooth bore, corrugated outside; really good resistance to abrasion and torsion. Wall thickness from 0,8 mm to 1,0 mm. Antistatic version with copper wire on request.*

*• Suction and transport of abrasive media such as powders, pellets, granulates, fibres and dust. It finds optimal application in the plastic, woodworking and ceramic industries and when a very good abrasion resistance is required.*



技术参数 / Technical data

代码 Code	内径 Ø Int.	最小壁厚 Min wall th.	最大壁厚 Max wall th.	重量 Weight	弯曲半径 Bending	耐负压 Vac.	每卷长度 Coil lgth.	体积 Vol.
	mm	mm	mm	g/m	mm	m H <sub>2</sub> O	m	m <sup>3</sup>
OP 01 030.0 000.0	30*	0,8	3,3	250	100	3,5	30	0,070
OP 01 032.0 000.0	32*	0,8	3,3	260	110	3	30	0,074
OP 01 035.0 000.0	35*	0,8	3,5	290	120	3	30	0,081
OP 01 038.0 000.0	38,1	0,8	3,5	310	130	3	30	0,087
OP 01 040.0 000.0	40	1,0	3,5	360	140	3	30	0,121
OP 01 045.0 000.0	45	1,0	3,8	450	160	3	30	0,135
OP 01 052.0 000.0	50,8	1,0	4,3	560	175	3	30	0,257
OP 01 060.0 000.0	60	1,0	4,3	650	200	3	30	0,296
OP 01 063.0 000.0	63,5	1,0	4,2	690	230	3	30	0,311
OP 01 065.0 000.0	65*	1,0	4,2	700	230	3	30	0,318
OP 01 070.0 000.0	70	1,0	4,7	760	250	3	30	0,344
OP 01 076.0 000.0	76,2	1,0	4,7	830	270	2,5	30	0,371
OP 01 080.0 000.0	80	1,0	5,2	910	290	2,5	30	0,694
OP 01 090.0 000.0	90	1,0	5,3	1080	360	2,5	30	0,774
OP 01 100.0 000.0	100	1,0	5,8	1260	400	2,5	30	0,859
OP 01 102.0 000.0	102	1,0	5,8	1290	400	2,5	30	0,874
OP 01 110.0 000.0	110*	1,0	6,0	1400	440	2,5	30	0,938
OP 01 120.0 000.0	120	1,0	6,0	1520	470	2,5	30	1,015
OP 01 127.0 000.0	127*	1,0	6,0	1610	500	2,5	30	1,425
OP 01 130.0 000.0	130*	1,0	6,1	1640	520	2,5	30	1,456
OP 01 140.0 000.0	140*	1,0	6,1	1810	570	2	30	1,219
OP 01 150.0 000.0	151,5*	1,0	6,5	2010	600	2	20	1,318
OP 01 152.0 000.0	152,8*	1,0	6,6	2030	600	2	20	1,325

\* 如有需求，请与我们的销售办公室联系，以获得更多的信息和数据 / \*Available on request, contact our sales office for more info and quantities

以上的报告技术数据均在温度23°C，50%湿度下测量的 / The technical data here reported were measured at 23°C with 50% humidity