SATURNO AQUAPOOL





白色PVC-P软管,耐碾压和抗震PVC螺旋增强。内壁 完全光滑,确保了介质的流动性。

出色的耐化学品、耐候、耐老化性。质轻,柔软,易搬动。

• 适用于游泳池和漩涡水疗中心中水的抽吸。

White PVC-P hose, reinforced with a crush-resistant and anti-shock rigid PVC spiral. Completely smooth inner surface to enhance the optimization of flow properties. Good chemical, weathering and ageing resistance. Lightweight, very flexible and easy to handle.

· Suction and transport of water in the treatment circuits of swimming pools and whirlpools at spas





PVC螺旋增强 Anti-shock rigid PVC spiral

技术参数·TE(CHNICAL DATA
----------	--------------





同系列产品 ITEMS IN THE SAME SERIES



型号	内径	外径	最小壁厚.	最大壁厚	重量	工作压力	爆破压力	耐负压	弯曲半径	每卷长度	体积
CODE	Ø INT.	Ø OUT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOL.
	mm	mm	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m³
QP0102000270*	20	27	3,4	3,5	330	7	21	10	50	30	0,037
QP0102500320*	25	32	3,3	3,5	390	7	21	10	60	30	0,049
QP0103180400*	31,8	40	4	4,1	590	6	18	10	80	30	0,069
QP0104300500*	43	50	3,4	3,5	640	6	18	10	110	30	0,103
QP0105500630*	55	63	3,9	4	940	5	15	10	140	30	0,272

SATURNO IDRO SE (cod. SI 06) p.78



NAUTILUS ODOR PROOF (cod. LU 01) p.79

The technical data here reported have been measured at 23°C with 50% umidity.

www.ipl-cn.com

^{*}如有需求,请与我们的销售办公室联系,以获得更多的信息和数据

^{*}Available on request, contact our sales office for more info and quantities. 以上报告的技术数据均在温度23℃,50%湿 度下测量